

## VELP Scientifica Solutions for Incubation



**FTC 120**

**FOC 120E**

**FOC 200E**

**FOC 120I**

**FOC 200I**

**FOC 200IL**

Internal transparent door				•	•	•
Total volume L	120	120	200	120	200	200
Temperature settings °C	20, constant	from 3 to 50	from 3 to 50	from 3 to 50	from 3 to 50	from 3 to 50
Temperature stability and homogeneity °C	± 0.5	± 0.5	± 0.5	± 0.5	± 0.5	± 0.5
Timer						controls lighting cycles
Lighting system						LED
TEMPSoft™ connection		•	•	•	•	•
Electronic thermoregulation system	Traditional	Auto-Tuning	Auto-Tuning	Auto-Tuning	Auto-Tuning	Auto-Tuning
Number of shelves supplied	2	2	3	2	3	3
Maximum number of shelves	4	4	5	4	5	5
Internal socket	2	2	2	2	2	2
Capacity (BOD System)	3 x BOD (EVO) Sensor System 6 2 x BOD Sensor System 10	3 x BOD (EVO) Sensor System 6 2 x BOD Sensor System 10	4 x BOD (EVO) Sensor System 6 2 x BOD Sensor System 10	2 x BOD (EVO) Sensor System 6 1 x BOD Sensor System 10	4 x BOD (EVO) Sensor System 6 1 x BOD Sensor System 10	4 x BOD (EVO) Sensor System 6 1 x BOD Sensor System 10
Dimensions (WxHxD) mm	540x905x550	540x905x550	540x1263x600	540x905x550	540x1263x600	540x1263x600
(in)	(21.3x35.6x21.7)	(21.3x35.6x21.7)	(21.3x49.7x21.7)	(21.3x35.6x21.7)	(21.3x49.7x21.7)	(21.3x49.7x21.7)
Weight						
Kg	36.0	36.0	46.3	36.0	46.3	50.0
(lb)	(79.4)	(79.4)	(102.1)	(79.4)	(102.1)	(110.2)
Power Supply	230 V	230 V	230 V	230 V	230 V	230 V
Power	120 W	120 W	400 W	120 W	400 W	400 W



[www.velp.com](http://www.velp.com)